

# SIDEBAR<sup>®</sup>

## BEVERAGE SYSTEMS



### 25 LITER HIGH CAPACITY SUPPLY RACK

**BR5G-01**

**Please read carefully prior to installing.**

First determine the location for the bottle rack, be certain you have room to remove the bottles from the rack after it has been installed. The supply lines from your SIDEBAR System should reach the bottom of each bottle.

**DO NOT SUSPEND THE RACK IN THE AIR** – The weight may damage the mounting surface, especially on mobile installations! The rack should be supported by the floor and secured to the wall.

Install the rack using lag bolts or large screws through the 3 (three) mounting plates.

Drill a **3/16"** hole in the top of each bottle; you may drill into the white cap or the sidewall of each bottle. **\*\*USE CARE IF DRILLING THE CAP, THE PLASTIC MAY CRACK WITH EXCESSIVE DRILL PRESURE\*\***

The supply lines from the SIDEBAR Pump will slide through the 3/16" holes. Cut a 45 degree point on the end of each suction line (this will prevent the tube from sticking to the bottom or sidewall of the bottle). Feed the lines to reach the bottom of each bottle.

Wash and rinse each bottle thoroughly prior to use.

Fill each bottle with your beverage of choice and place in the rack.

Insert the 1/8" intake line through each bottle. Make certain the suction line is forced to the bottom of each bottle.

*Cutting a 45 degree 'tip' on the end of each line will prevent the suction line from adhering to the bottom of the bottle.*

Feel free to contact us with any questions or product support.